

## CSE Series Pendant Stations

### Features

- Safety yellow high impact fiber reinforced plastic body
- NEMA 4X watertight for indoor and outdoor applications
- Ambient temperature range: -20 to 158F (-29 to 70C)
- UL and cUL listed capabilities
- Choice of single-speed, two-speed, or on-off



Electrical Contact Ratings (OSHA Regulation, Section 1910.70, Overhead and Gantry Cranes, limits the voltage of pendant push buttons to 150 Vac or 300 Vdc.)									
AC NEMA600							DC NEMAP600		
Volts	Inductive 35% Power Factor				Continuous Carrying Amperes	Resistive 75% Power Factor Make, Break and Continuous Carrying Amperes	Volts	Inductive and Resistive	
	Make		Break					Make and Break Amperes	Continuous Carrying Amperes
	A	VA	A	VA					
120	60	7200	6	720	10	10	120	1.1	5
240	30	7200	3	720	10	10	240	0.55	5
480	15	7200	1.5	720	10	10	600	0.2	5
600	12	7200	1.2	720	10	10			

### Wiring Diagrams

Part Number	CSE272	CSE275	CSE282
Description	Single – d <sup>†</sup> i Speed	Momentary (on/off)	Two – d <sup>†</sup> Speed
Wiring Diagrams			
Features	mechanical interlocked		mechanical interlocked

